







Product Code: 243431 EAN: 5901583243431

## LED line® module 4 SMD2835 OSRAM LED 12V 3W 6000-6500K 170° OPTO

## Description

High luminous efficacy ensured by high quality OSRAM branded LEDs. Manufacturer issues a 7-year warranty for this product. The item achieves luminous efficacy at 95lm/W or more. This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



The item achieves luminous efficacy at 95lm/W or more.



Manufacturer issues a 7-year warranty for this product.



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



 $\label{thm:local_equality} \mbox{High quality OSRAM branded } \mbox{LEDs.}$ 



Voltage range and voltage type



Material (housing)



LED quantity



Lifespan



Ambient temperature suitable for operation



Beam angle



LED type



Compatible dimmer type



Number of on/off cycles



Parameter	Value
Colour temperature	6000-6500K
Colour of the light	white
Luminous efficacy	95lm/W
Current	250mA
Ra colour rendering index	80
Energy class	A++
Colour	beige
Lamp's warm-up time to 60%	1
Lumen maintenance factor (LLMF)	>0,7
Product weight with packaging (g)	>0,7
Full box quantity	60
Master carton weight (kg)	1,5
Supply voltage range and voltage type	12 DC
Beam angle	170°
Material (housing)	PVC
LED type	SMD2835

Parameter	Value
LED quantity	4
Not dimmable	TAK
Compatible dimmer type	PWM
Lifespan	70000
Number of on/off cycles	50000
Height	10 mm
Length	52 mm
Ambient temperature suitable for operation	-40°C/+55°C
For indoor and outdoor use	TAK
LED manufacturer	OSRAM
Warranty (years)	7
Flicker Free	T
Width	46
IP protection rating	65
Luminous flux	285lm
Wattage	3