

Technical Datasheet **tasker® C114 – 2x0,25 mm²** Low Capacity Balanced Microphone Cable



A	B	C	D	E
---	---	---	---	---

CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Pre Made Audio Cables and Microphones.

- A:** PVC Sheath. Available in different color.
 Outer cable Diam. Ø 6,00 (±0,20) mm.
B: Shielding O.F.C. red copper Spiral covering 100%.
C: The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
D: Core Insulation with a compact PE, colored one Orange and one Transparent. Diam. Ø 1,50 (±0,20) mm.
E: O.F.C. red copper, formation 8x0,20 mm.
 Nom. Cross section 2x0,25 mm².

MARKING **tasker® C 114 2x0.25 mm² - O.F.C. Low Capacitance Flex** Microphone Cable
 Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, or Metallic Armored.

NOTE Also available with other sheath color, see tasker C260.

Cable Properties

Conductor Resistance	75 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	90 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			