



## FFKu-EM-F-UV black

33412



## Product description:

FFKu-EM-F-UV Highspeed is a medium duty corrugated plastic conduit made from modified PVC, in black, with low friction inner surface, non-flame propagating, UV stabilised.

This corrugated plastic conduit is used in concrete and installations in cavity walls as well as outdoor installations. Advantages are its medium compressive strength and the low friction inner surface. This allows easy insertion of cables and wires over long distances.



VDE 0605  
DIN EN 61386-22  
minimum compressive strength: 750 N/5 cm



## Special features

UV-resistant for up to 10 years.

Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Pallet content m	Bend radius > mm
254 30 016	16	10,9	16,0	50	m	2,350	2.100	70
254 30 020	20	14,2	20,0	50	m	3,300	1.500	90
254 30 025	25	18,6	25,0	50	m	4,750	1.200	110
254 30 032	32	24,3	32,0	25	m	3,100	600	130
254 30 040	40	31,3	40,0	25	m	4,200	400	170
254 30 050**	50	40,0	50,0	25	m	5,450	400	220
254 30 063**	63	50,5	63,0	25	m	7,875	150	300

Classification	Code	Meaning	Classification	Code	Meaning
Compressive strength	3	medium (750 N)	Protection against solids	4	Foreign matter >= 1.0 mm
Impact strength	3	medium (2.0 kg/100 mm)	Protection against water	0	Not specified
Minimum temperature	4	- 25 °C	Corrosion protection	0	Not specified
Maximum temperature	1	+ 60 °C	Tensile strength	0	Not defined
Bending behaviour	2	pliable	Fire behaviour	1	Non flame propagating
Electrical characteristics	2	Insulation	Suspended load	0	Not defined

## Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-22:2011 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

Outside diameter according to DIN EN 60423 / IEC 60423

All dimensions without tolerances are for information only.

FRÄNKISCHE Rohrwerke Gebr. Kirchner GmbH & Co. KG | Hellinger Str. 1 | 97486 Königsberg/Bayern  
Tel. +49 9525 88-8123 | Fax +49 9525 88-2151 | info.elektro@fraenkische.de | www.fraenkische.com

Subject to change without notice.

Page 1 of 2

Last modified: 25.01.19



## FFKu-EM-F-UV black

33412

## Material properties

Zero halogen	DIN VDE V 0604-2-100	
Low smoke	DIN EN 61034-2	
<b>Non-flame propagating</b>	<b>DIN EN 61386-1</b>	•
<b>UV-resistant</b>	<b>DIN 53387</b>	•
<b>Highspeed</b>		•

## Fields of application

<b>on plaster</b>	• <b>machines</b>	•
<b>under plaster</b>	• hot asphalt	
<b>on wood</b>	• <b>under screed</b>	•
<b>underground installation</b>	• <b>prefabricated construction</b>	•
<b>in concrete</b>	• <b>outdoor</b>	•

## Chemical properties

<b>Resistant to</b>	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, nitric acid, hydrochloric acid, sulfuric acid, turpentine, detergent
<b>Limitedly resistant to</b>	gaseous dry chlorine
<b>Not resistant to</b>	benzene, beer

## Accessories

Push-fit coupling	SMSKu-E-UV black	225 51 ...
Clamp	clipfix-UV black	225 71 ...

## Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

## Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

