


## 33885 IQ-LED FL-10W-NW-SE

LED floodlight

5905339338853



Kanlux IQ FL floodlights are unique products. Their automatic production allows ensuring the highest quality and repeatability of lighting parameters. They include brand LEDs with a life span of 50,000 hours, which is also their additional advantage. The use of the highest quality components allows us to provide our customers with a five-year warranty for the whole series of Kanlux IQ FL floodlights.

### GENERAL DATA:

**Colour:** black  
**Place of assembly:** wall mounted, ceiling mounted  
**Place of application:** outdoors  
**Minimum distance from the illuminated object:** 1m  
**Compatible with a dimmer:** no  
**RAL:** 7024  
**Wykrywanie ruchu:** yes  
**Width [mm]:** 135  
**Height [mm]:** 164  
**Wire length [m]:** 0.3  
**Depth [mm]:** 56  
**Mercury content:** no  
**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 10  
**Class of protection against electric shock:** I  
**Lampshade material:** Tempered glass  
**Diode type:** LED SMD  
**Luminous flux [lm]:** 1200  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** 1200  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** in sphere (360°)  
**Colour temperature:** white  
**Correlated colour temperature [K]:** 4000  
**Colour consistency in McAdam ellipses:**  $\leq 6$   
**Colour rendering index:** 80  
**Service life [h]:** 50000

## 33885 IQ-LED FL-10W-NW-SE

LED floodlight

**Number of on/off cycles:**  $\geq 25000$   
**Lighting angle [°]:** 100  
**Luminous efficiency of the lamp [lm/W]:** 120  
**Ambient temperature range to which the product can be exposed:**  $-30 \div 50$   
**Enclosure material:** Metal  
**Sensor type:** PIR  
**Connection type:** Free cable ends  
**Wire type:** H05RN-F  
**Wire diameter [mm<sup>2</sup>]:** 1  
**Sensor-operation time [second-minute]:** 10-7  
**Lamp-heating time [s]:**  $\leq 1$   
**Lamp-ignition time [s]:**  $\leq 0,5$   
**sensor working angle [°]:** 120  
**Illumination-level setpoint by which the sensor detects movement [lx]:** 10-2000  
**The fixture is movable vertically [°]:** 180  
**IP class:** 44  
**Sensor range[m]:** max 8

### LOGISTIC DATA:

**Unit of measurement:** unit  
**Packaging method:** 20  
**Number of units in the secondary packaging:** 1  
**Number of units in the packaging:** 20  
**Grammage [g]:** 0.46  
**Weight of a cardboard box [kg]:** 0.0092  
**Width of a cardboard box [cm]:** 30  
**Height of a cardboard box [cm]:** 19  
**Length of a cardboard box [cm]:** 62  
**Volume of a cardboard box [m<sup>3</sup>]:** 0.03534

### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website